This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method for individualizing a hearing aid in adaptation to a loudness perception of an individual, said method ~~consisting of the following~~ comprising the steps of:

- ~~measurement~~ measuring and quantifying ~~quantification by parameters of the~~ loudness perception parameters of the individual, weighted by a first factor;
- weighting of ~~a~~ normal loudness perception ~~and its~~ parameters by a second factor;

combining the weighted loudness perception parameters of the individual with the weighted normal loudness perception parameters to define a weighted loudness parameter; and ~~use of the weighted loudness perception and its parameters~~ using the weighted loudness parameter for adjusting the hearing aid.

2. (previously presented) The method as in claim 1, wherein compression and/or amplification is/are adjusted in the hearing aid, for which purpose the compression and, respectively, the amplification are each determined as a function of frequency.

3. (currently amended) ~~The~~ A method ~~as in claim 2,~~ for individualizing a hearing aid in adaptation to a loudness perception of an individual, said method comprising the steps

of:

adjusting the hearing aid using one or both of (1) measured and quantified loudness perception parameters of the individual weighted by a first factor and (2) normal loudness perception parameters weighted by a second factor; and

adjusting compression and/or amplification in the hearing aid, for which purpose the compression and, respectively, the amplification are each determined as a function of frequency, wherein

for determining the compression, the loudness perception of the individual is quantified by means of a HVLS/LOHL factor which is determined by loudness scaling at a minimum of one frequency.

4. (currently amended) The method as in claim 3, wherein the HVLS/LOHL factor is modeled using the equation $\log_{10}(\alpha) = a_a \times HV/HL + b_a \times \log(HV/HL) + VP_{consta}$ where

[-] α = a gradient of the loudness function,

[-] HV/HL = a hearing loss in dB,

[-] a_a, b_a = constant function parameter, and

[-] VP_{consta} ~~Vp_{consta}~~ = an individual function parameter which adapts the HVLS/LOHL factor to data sampling points α_1, α_2, α_3, ...,

and that VP_{consta} is determined on the basis of a loudness scaling performed at a minimum of one frequency.

5. (previously presented) The method as in claim 2, wherein for determining the amplification, the loudness

perception of the individual is quantified by means of an HVL0/HLL0 factor which is defined by loudness scaling at a minimum of one frequency.

6. (previously presented) The method as in claim 5, wherein the HVL0/HLL0 factor is modeled using the equation

$$L_0 = a_L \times HV/HL + b_L \times \log(HV/HL) + VP_{constL},$$

where

[-] L_0 = a level of loudness=0,

[-] HV/HL = a hearing loss in dB,

[-] a_L, b_L = a constant function parameter, and

[-] VP_{constL} = an individual function parameter which adapts the HL0/HLL0 function to the data sampling points L_{01}, L_{02}, L_{03}, ...,

and that VP_{constL} is determined on the basis of a loudness scaling performed at a minimum of one frequency.

7. (currently amended) The method as in one of the claims 4 to 6 and 11, wherein the hearing loss is used for determining the frequencies at which loudness scaling is performed.

8. (currently amended) The method as in one of the claims 3 to 6 and 10 to 11, wherein the value of the weighted factors depends on the assumed and/or determined accuracy of the loudness scaling data.

9. (currently amended) The method as in claim 8, further comprising the selection of a value of ~~2/3~~ 1/3 for the first factor and/or a value of ~~1/3~~ 2/3 for the second factor.

10. (new) The method as in claim 2, wherein, for determining the compression, the loudness perception of the individual is quantified by means of a HVLS/LOHL factor which is determined by loudness scaling at a minimum of one frequency.

11. (new) The method as in claim 10, wherein the HVLS/LOHL factor is modeled using the equation $\log_{10}(\alpha) = a_a \times HV/HL + b_a \times \log(HV/HL) + VP_{consta}$ where

[-] α = a gradient of the loudness function,

[-] HV/HL = a hearing loss in dB,

[-] a_a, b_a = constant function parameter, and

[-] $\underline{VP_{consta}}$ ~~Vp_{consta}~~ = an individual function parameter which adapts the HVLS/LOHL factor to data sampling points α_1, α_2, α_3, ...,

and that VP_{consta} is determined on the basis of a loudness scaling performed at a minimum of one frequency.

12. (new) The method as in claim 1, further comprising the selection of a value of 2/3 for the first factor and/or a value of 1/3 for the second factor.